

Rating	16A 125VAC 1/3HP 10A 250VAC 1/2HP	cULus	Mounting Hole	Circuit Structure												
	10A 125V~,6(3)A 250V~															
Contact R	50m ohm Max.		<table border="1"> <thead> <tr> <th>Thickness</th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>0.75...1.25</td> <td>19.2-0.1</td> <td>13+0.1</td> </tr> <tr> <td>1.25...2</td> <td>19.4-0.1</td> <td>13+0.1</td> </tr> <tr> <td>2...3</td> <td>19.8-0.1</td> <td>13+0.1</td> </tr> </tbody> </table>	Thickness		X	Y	0.75...1.25	19.2-0.1	13+0.1	1.25...2	19.4-0.1	13+0.1	2...3	19.8-0.1	13+0.1
Thickness	X			Y												
0.75...1.25	19.2-0.1			13+0.1												
1.25...2	19.4-0.1	13+0.1														
2...3	19.8-0.1	13+0.1														
Insulation R	DC 500V 100M ohm Min.															
Dielectric Strength	AC 1500V 1 minute															
Operation Temperature	-20°C~85°C															
Circuit	4P SPST ON-OFF (LED)															

