



Cubed Solid State Pumps

- **Application:** The highest quality and dependable Lift Pump and Priming Pump for Diesel Injection Systems. OEM for most Diesel Engines, Heater Systems, Marine Engines, Generators. Agriculture and Construction Equipment. OEM in numerous Military application. Universal Pump for most Carburetor equipped applications.
- **Fuel Compatibility:** No rubber diaphragms or valves to swell or deteriorate in alcohol blended fuels. Compatible with leaded and unleaded gasoline, diesel fuel, blended alcohol fuels, and fuel additives.
- **Solid State Reliability:** Proven on thousands of original equipment applications. No electrical contacts. No bearings or diaphragms to wear out or fatigue. Lasts four to five times longer than many other electric fuel pumps.
- **Easy to Install:** Two-bolt installation plus the small size makes installation easy. For best results, mount the pump close to the fluid or fuel tank and below the liquid level.
- **Eliminates Vapor Lock:** When properly installed on most vehicles a constant, smooth, dependable supply of fuel under pressure is assured in the hottest weather or in high altitudes.
- **Features:**
 - 12 - 84 inches minimum dry lift
 - 14 - 34 GPH
 - 2 - 11.5 PSI
 - Transient Protection
 - State of the art Electronics
 - Sealed Electronics
 - Reverse Polarity protection
 - Built in check valve
 - Built in Anti-Siphon Valve
 - UL Certified
 - 1.6 amp average
 - Self Priming and Self Regulating
 - 18 ounces and 3 inches
 - Corrosion Resistant over 100 hours of salt spray
 - Built in Pressure Relief

